

Section 17 Town 6 Range 5-

Dec 10 1847

I commenced a Survey of Section 17, T. 6, R. 5-
for *Wm Farnham*

Legal Survey

H. G. Schloot as Deputy

C. B.

Chas V Miller
Surveyor Greene County.

Var.

Course.	Point of Beginning.	Chains Distance.	Corrected Bearings.
---------	---------------------	------------------	---------------------

stone
Sec 20
NE
stone

North from $S\frac{1}{4}$ NE sec 20-6-5- 1324' to cen $\frac{1}{4}$ NE
2648 to $N\frac{1}{4}$ NE
West from $S\frac{1}{4}$ sec 17-6-5- 1307.9' to $S\frac{1}{4}$ SE sec 17-6-5-
2615.8 to SE sec 17-6-5-
North from $S\frac{1}{4}$ SE sec 17-6-5- 1320' to cen SE sec 17-6-5-
2640' to $N\frac{1}{4}$ SE sec 17-6-5-
North $\frac{1}{4}$ SE sec 17-6-5- stone therein river Bottom
Cen SE 17-6-5- 4x4 concrete marker
36" twin maple south 3.7'
30 " " East 21'
South $\frac{1}{4}$ SE sec 17-6-5- Stake
SE sec 17-6-5- Stone gone but stump of witness trees there
New witness 6" twin walnut north 36'
Beech SE 17.7'

 $S\frac{1}{4}$ NE sec 20-6-5- stone in road
Cen $\frac{1}{4}$ NE sec 20-6-5- stake in road
concrete post west 15.0'

CORNER ESTABLISHED.	Monument.	Device.	WITNESS POINTS OR BEARING TREES.	Mark or Dia. in Inches.	COURSE.	Links Distant.	REMARKS.
---------------------	-----------	---------	----------------------------------	-------------------------	---------	----------------	----------